

INFINITY NV-3504-H1/4P

Specification

Model	NV-3504-H1/4P	
Video/Audio input	IP video input	4-ch
	Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)
Network	Incoming bandwidth	40Mbps
	Outgoing bandwidth	80Mbps
	Remote connection	32
Video/Audio output	Recording resolution	6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
	Frame rate	Main stream: 50 fps (P) / 60 fps (N)
		Sub-stream: 50 fps (P) / 60 fps (N)
	HDMI/VGA output	1-ch, resolution: 1920 × 1080 /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
Decoding	Audio output	1-ch, RCA (Linear, 1kΩ)
	Live view / Playback resolution	6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Hard disk	Capability	4-ch@1080p
	SATA	1 SATA interfaces for 1 HDD
External interface	Capacity	Up to 4TB for each disk
	Network interface	1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface
	USB interface	1 × USB 2.0 and 1 × USB 3.0
PoE	Alarm in/out (Optional)	4/1
	Interface	4 independent 100 Mbps PoE network interfaces
	Max. Power	50W
General	Supported standard	AF and AT
	Power supply	48V DC
	Consumption (without hard disk and PoE)	≤10W
	Working temperature	-10 °C ~ +55 °C (+14 °F ~ +131 °F)
	Working humidity	10 % ~ 90 %
	Chassis	1U chassis
	Dimensions (W × D × H)	315 × 230 × 45mm (12.4" × 9.1" × 1.8")
	Weight (without hard disk)	≤ 1 kg (2.2 lb)

Key Feature

- Third-party network cameras supported
- Up to 6 Megapixels resolution recording
- HDMI and VGA output at up to 1920×1080P resolution
- 4-ch network cameras can be connected with 40M incoming bandwidth
- Up to 1 SATA interfaces
- Plug & Play with up to 4 independent PoE network interfaces
- Support network detection, including network delay, packet loss, etc